

## Data sheet

### CM 201 (201-1AA00)

#### Technical data

|                                 |   |
|---------------------------------|---|
| <b>Order no.</b>                | <b>201-1AA00</b>                                    |
| Type                            | CM 201  |
| <b>General information</b>      |   |
| Note                            | -   |
| Features                        | Dual terminals<br>2x11 clamps, gray/gray<br>Passive |
| <b>Clamp parameter</b>          |   |
| Terminal voltage max.           | DC 60 V   |
| Terminal current max.           | 10 A  |
| <b>Isolated group</b>           |   |
| Number of clamps                | 11-11   |
| Color of clamps                 | grey-grey   |
| Binding of potential            | unbound-unbound                                     |
| Potential group current, max.   | 10 A-10 A   |
| <b>Housing</b>                  |   |
| Material                        | PPE / PA 6.6  |
| Mounting                        | Profile rail 35 mm                                  |
| <b>Mechanical data</b>          |   |
| Dimensions (WxHxD)              | 25.4 mm x 76 mm x 80 mm                             |
| Weight                          | 90 g  |
| <b>Environmental conditions</b> |   |
| Operating temperature           | 0 °C to 60 °C                                       |
| Storage temperature             | -25 °C to 70 °C                                     |
| <b>Certifications</b>           |   |
| UL certification                | yes   |
| KC certification                | -   |