

## Data sheet

### SM 222 (222-1BH10)

#### Technical data

<b>Order no.</b>	<b>222-1BH10</b>
------------------	------------------

Type	SM 222
------	--------

#### General information

Note	-
------	---

Features	16 outputs Output current 1 A
----------	----------------------------------

#### Current consumption/power loss

Current consumption from backplane bus	120 mA
--	--------

Power loss	3.5 W
------------	-------

#### Technical data digital outputs

Number of outputs	16
-------------------	----

Cable length, shielded	1000 m
------------------------	--------

Cable length, unshielded	600 m
--------------------------	-------

Rated load voltage	DC 20.4...28.8 V
--------------------	------------------

Current consumption from load voltage L+ (without load)	10 mA
---	-------

Total current per group, horizontal configuration, 40°C	10 A
---	------

Total current per group, horizontal configuration, 60°C	10 A
---	------

Total current per group, vertical configuration	10 A
---	------

Output current at signal "1", rated value	1 A
---	-----

Output delay of "0" to "1"	150 µs
----------------------------	--------

Output delay of "1" to "0"	100 µs
----------------------------	--------

Minimum load current	-
----------------------	---

Lamp load	5 W
-----------	-----

Parallel switching of outputs for redundant control of a load	not possible
---	--------------

Parallel switching of outputs for increased power	not possible
---	--------------

Actuation of digital input	yes
----------------------------	-----

Switching frequency with resistive load	max. 1000 Hz
---	--------------

Switching frequency with inductive load	max. 0.5 Hz
---	-------------

Switching frequency on lamp load	max. 10 Hz
----------------------------------	------------

Internal limitation of inductive shut-off voltage	L+ (-52 V)
---	------------

Short-circuit protection of output	yes, electronic
------------------------------------	-----------------

Trigger level	1.5 A
---------------	-------

Number of operating cycle of relay outputs	-
--	---

Switching capacity of contacts	-
--------------------------------	---

Output data size	2 Byte
------------------	--------

#### Status information, alarms, diagnostics

Status display	green LED per channel
----------------	-----------------------

Interrupts	no
------------	----

Process alarm	no
---------------	----

Diagnostic interrupt	no
----------------------	----

Diagnostic functions	no
----------------------	----

Diagnostics information read-out	none
Supply voltage display	green LED per group
Group error display	red SF LED
Channel error display	none

### Isolation

Between channels	-
Between channels of groups to	16
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

### Datasizes

Input bytes	0
Output bytes	2
Parameter bytes	0
Diagnostic bytes	0

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 88 mm
Weight	90 g

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL certification	yes
KC certification	-