

## Data sheet

### IM 261, Row interface (261-1CA00)

#### Technical data

<b>Order no.</b>	<b>261-1CA00</b>
Type	IM 261, Row interface

#### General information

Note	-
Features	Only be used in conjunction with the PC 288 or a CPU

#### Technical data power supply

Power supply (rated value)	-
Power supply (permitted range)	-
Reverse polarity protection	-
Current consumption (no-load operation)	-
Current consumption (rated value)	-
Inrush current	-
Max. current drain at backplane bus	1.5 A
Max. current drain load supply	-
Power loss	1 W

#### Status information, alarms, diagnostics

Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	yes
Group error display	none
Channel error display	none

#### Hardware configuration

Racks, max.	1
Modules per rack, max.	16
Number of digital modules, max.	16
Number of analog modules, max.	16

#### Housing

Material	PPE
Mounting	Profile rail 35 mm

#### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Weight	90 g

#### Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature -25 °C to 70 °C

---

### Certifications

---

UL certification yes

---

KC certification -

---