

Data sheet CPU 314ST/DPM (314-6CF03)

Technical data

Order no.	314-6CF03
Туре	CPU 314ST/DPM
General information	
Note	-
Features	SPEED7 technology, SPEED-Bus 8 x DI, 8 x DIO, 4 x AI, 2 x AO, 1 x AI Pt100 512 kB work memory Memory extension (max. 2 MB) PROFIBUS-DP master / PtP (switchable) Also configurable via TIA-Portal
SPEED-Bus	yes
Technical data power supply	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.428.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	300 mA
Current consumption (rated value)	1 A
Inrush current	5 A
l²t	0.5 A²s
Max. current drain at backplane bus	2.5 A
Max. current drain load supply	-
Power loss	14 W
Technical data digital inputs	
Number of inputs	8
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 24 V
Reverse polarity protection of rated load voltage	yes
Current consumption from load voltage L+ (without load)	70 mA
Rated value	DC 24 V
Input voltage for signal "0"	DC 05 V
Input voltage for signal "1"	DC 1528.8 V
Input voltage hysteresis	-
Frequency range	-
Input resistance	-
Input current for signal "1"	6 mA
Connection of Two-Wire-BEROs possible	yes
Max. permissible BERO quiescent current	1.5 mA
Input delay of "0" to "1"	parameterizable 2.56µs - 40ms
Input delay of "1" to "0"	parameterizable 2.56µs - 40ms
Number of simultaneously utilizable inputs horizontal configuration	8
Number of simultaneously utilizable inputs vertical configuration	8



Input characteristic curve	IEC 61131-2, type 1	A YASKAWA COMPANY
Initial data size	34 Byte	
Technical data digital outputs		
Number of outputs	8	
Cable length, shielded	1000 m	
Cable length, unshielded	600 m	
Rated load voltage	DC 24 V	
Reverse polarity protection of rated load voltage	-	
Current consumption from load voltage L+ (without load)	30 mA	
Total current per group, horizontal configuration, 40°C	4 A	
Total current per group, horizontal configuration, 60°C	3 A	
Total current per group, vertical configuration	3 A	
Output voltage signal "1" at min. current	L+ (-0.8 V)	
Output voltage signal "1" at max. current	L+ (-0.8 V)	
Output current at signal "1", rated value	0.5 A	
Output current, permitted range to 40°C	5 mA to 0.6 A	
Output current, permitted range to 60°C	5 mA to 0.6 A	
Output current at signal "0" max. (residual current)	100 µA	
Output delay of "0" to "1"	100 µs	
Output delay of "1" to "0"	100 µs	
Minimum load current	-	
Lamp load	5 W	
Parallel switching of outputs for redundant control of a load	possible	
Parallel switching of outputs for increased power	not possible	
Actuation of digital input	yes	
Switching frequency with resistive load	max. 2.5 kHz	
Switching frequency with inductive load	max. 0.5 Hz	
Switching frequency on lamp load	max. 2.5 kHz	
Internal limitation of inductive shut-off voltage	L+ (-52 V)	
Short-circuit protection of output	yes, electronic	
Trigger level	1 A	
Number of operating cycle of relay outputs	-	
Switching capacity of contacts	-	
Output data size	18 Byte	
Technical data analog inputs		
Number of inputs	5	
Cable length, shielded	200 m	
Rated load voltage	DC 24 V	
Reverse polarity protection of rated load voltage	yes	
Current consumption from load voltage L+ (without load)	85 mA	
Voltage inputs	yes	
Min. input resistance (voltage range)	120 kOhm	
Input voltage ranges	-10 V +10 V 0 V +10 V	
Operational limit of voltage ranges	+/-0.3%	
Operational limit of voltage ranges with SFU	-	
Basic error limit voltage ranges	+/-0.3%	
Basic error limit voltage ranges with SFU	-	

© by VIPA GmbH, Ohmstr. 4, 91074 Herzogenaurach, Germany All data with reservation and subject to change. Publish date: 26.07.2016



Destruction limit voltage	max. 15V	A YASKAWA COMPANY
Current inputs	yes	
Max. input resistance (current range)	85 Ohm	
Input current ranges	-20 mA +20 mA 0 mA +20 mA +4 mA +20 mA	
Operational limit of current ranges	+/-0.3%	
Operational limit of current ranges with SFU	-	
Basic error limit current ranges	+/-0.2%	
Radical error limit current ranges with SFU	-	
Destruction limit current inputs (electrical current)	max. 50mA	
Destruction limit current inputs (voltage)	max. 15V	
Resistance inputs	yes	
Resistance ranges	0 600 Ohm	
Operational limit of resistor ranges	+/-0.4%	
Operational limit of resistor ranges with SFU	-	
Basic error limit	+/-0.2%	
Basic error limit with SFU	-	
Destruction limit resistance inputs	max. 15V	
Resistance thermometer inputs	yes	
Resistance thermometer ranges	Pt100 Pt1000 Ni100 Ni1000	
Operational limit of resistance thermometer ranges	+/-0.6%	
Operational limit of resistance thermometer ranges with SFU	-	
Basic error limit thermoresistor ranges	+/-0.4%	
Basic error limit thermoresistor ranges with SFU	-	
Destruction limit resistance thermometer inputs	max. 15V	
Thermocouple inputs	-	
Thermocouple ranges	-	
Operational limit of thermocouple ranges	-	
Operational limit of thermocouple ranges with SFU	-	
Basic error limit thermoelement ranges	-	
Basic error limit thermoelement ranges with SFU	-	
Destruction limit thermocouple inputs	-	
Programmable temperature compensation	-	
External temperature compensation	-	
Internal temperature compensation	-	
Technical unit of temperature measurement	°C	
Resolution in bit	12	
Measurement principle	Sigma-Delta	
Basic conversion time	6 ms	
Noise suppression for frequency	80 dB	
Initial data size	10 Byte	
Technical data analog outputs		
Number of outputs	2	
Cable length, shielded	200 m	
Rated load voltage	DC 24 V	
Reverse polarity protection of rated load voltage	yes	



Current consumption from load voltage L+ (without load)

Voltage output short-circuit protection	-
Voltage outputs	yes
Min. load resistance (voltage range)	1 kOhm
Max. capacitive load (current range)	1 µF
Max. inductive load (current range)	30 mA
Output voltage ranges	-10 V +10 V 0 V +10 V
Operational limit of voltage ranges	+/-0.4%
Basic error limit voltage ranges with SFU	+/-0.3%
Destruction limit against external applied voltage	max. 15V
Current outputs	yes
Max. in load resistance (current range)	500 Ohm
Max. inductive load (current range)	10 mH
Typ. open circuit voltage current output	16 V
Output current ranges	-20 mA +20 mA 0 mA +20 mA +4 mA +20 mA
Operational limit of current ranges	+/-0.4%
Radical error limit current ranges with SFU	+/-0.3%
Destruction limit against external applied voltage	max. 15V
Settling time for ohmic load	0.2 ms
Settling time for capacitive load	0.5 ms
Settling time for inductive load	0.75 ms
Resolution in bit	12
Conversion time	1 ms
Substitute value can be applied	yes
Output data size	4 Byte
Technical data counters	
Number of counters	4
Counter width	32 Bit
Maximum input frequency	100 kHz
Maximum count frequency	100 kHz
Mode incremental encoder	yes
Mode pulse / direction	yes
Mode pulse	yes
Mode frequency counter	-
Mode period measurement	-
Gate input available	yes
Latch input available	yes
Reset input available	yes
Counter output available	yes
Load and working memory	
Load memory, integrated	2 MB
Load memory, integrated Load memory, maximum	2 MB 2 MB
Load memory, integrated Load memory, maximum Work memory, integrated	2 MB 2 MB 512 KB
Load memory, integrated Load memory, maximum Work memory, integrated Work memory, maximal	2 MB 2 MB 512 KB 2 MB
Load memory, integrated Load memory, maximum Work memory, integrated Work memory, maximal Memory divided in 50% program / 50% data	2 MB 2 MB 512 KB 2 MB yes

_



	PT 2.1	
Hardward	contiguinati	00
naluwale	connuurau	OIL

Racks, max.	4
Modules per rack, max.	8 in multiple-, 32 in a single-rack configuration
Number of integrated DP master	1
Number of DP master via CP	4
Operable function modules	8
Operable communication modules PtP	8
Operable communication modules LAN	8

Status information, alarms, diagnostics

Status display	yes
Interrupts	yes
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes
Diagnostics information read-out	possible
Supply voltage display	green LED
Group error display	red SF LED
Channel error display	red LED per group

Isolation

Between channels	yes
Between channels of groups to	8
Between channels and backplane bus	yes
Between channels and power supply	-
Max. potential difference between circuits	DC 75 V/ AC 50 V
Max. potential difference between inputs (Ucm)	-
Max. potential difference between Mana and Mintern (Uiso)	-
Max. potential difference between inputs and Mana (Ucm)	-
Max. potential difference between inputs and Mintern (Uiso)	-
Max. potential difference between Mintern and outputs	-
Insulation tested with	DC 500 V
Command processing times	
Bit instructions, min.	0.01 µs

· · · · · · · · · · · · · · · · · · ·	
Word instruction, min.	0.01 µs
Double integer arithmetic, min.	0.01 µs
Floating-point arithmetic, min.	0.06 µs

Timers/Counters and their retentive characteristics

Number of S7 counters	512
Number of S7 times	512

Data range and retentive characteristic

Number of flags	8192 Byte
Number of data blocks	4095
Max. data blocks size	64 KB
Max. local data size per execution level	1024 Byte



Blocks	
Number of OBs	23
Number of FBs	2048
Number of FCs	2048
Maximum nesting depth per priority class	8
Maximum nesting depth additional within an error OB	4
Time	
Real-time clock buffered	yes
Clock buffered period (min.)	6 w
Accuracy (max. deviation per day)	10 s
Number of operating hours counter	8
Clock synchronization	yes
Synchronization via MPI	Master/Slave
Synchronization via Ethernet (NTP)	no
Address areas (I/O)	
Input I/O address area	8192 Byte
Output I/O address area	8192 Byte
Input process image maximal	2048 Byte
Output process image maximal	2048 Byte
Digital inputs	65536
Digital outputs	65536
Digital inputs central	1032
Digital outputs central	1032
Integrated digital inputs	8
Integrated digital outputs	8
Analog inputs	1024
Analog outputs	1024
Analog inputs, central	261
Analog outputs, central	258
Integrated analog inputs	5
Integrated analog outputs	2
Communication functions	
PG/OP channel	yes
Global data communication	yes
Number of GD circuits, max.	4
Size of GD packets, max.	22 Byte
S7 basic communication	yes
S7 basic communication, user data per job	76 Byte
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
S7 communication, user data per job	160 Byte
Number of connections, max.	32
PWM data	
PWM channels	-



PWM time basis	-	A YASKAWA COMPANY
Period length	-	
Minimum pulse width	-	
Type of output	_	

Functionality Sub-D interfaces

Туре	X2
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	yes
MPI	yes
MP²I (MPI/RS232)	-
DP master	-
DP slave	-
Point-to-point interface	-
5V DC Power supply	max. 90mA, isolated
24V DC Power supply	max. 100mA, non-isolated

Туре	Х3
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	yes
MPI	-
MP²I (MPI/RS232)	-
DP master	yes
DP slave	yes
Point-to-point interface	yes
5V DC Power supply	max. 90mA, isolated
24V DC Power supply	max. 100mA, non-isolated

Functionality MPI

-	
Number of connections, max.	32
PG/OP channel	yes
Routing	yes
Global data communication	yes
S7 basic communication	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
Transmission speed, min.	19.2 kbit/s
Transmission speed, max.	12 Mbit/s

Functionality PROFIBUS master

PG/OP channel	yes
Routing	yes
S7 basic communication	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-



Activation/deactivation of DP slaves	yes	A YASKAWA COMPANY
Direct data exchange (slave-to-slave communication)	-	
DPV1	yes	
Transmission speed, min.	9.6 kbit/s	
Transmission speed, max.	12 Mbit/s	
Number of DP slaves, max.	124	
Address range inputs, max.	1 KB	
Address range outputs, max.	1 KB	
User data inputs per slave, max.	244 Byte	
User data outputs per slave, max.	244 Byte	
Functionality PROFIBUS slave		
PG/OP channel	yes	
Routing	yes	
S7 communication	yes	
S7 communication as server	yes	
S7 communication as client		
Direct data exchange (slave-to-slave communication)	-	
DPV1	yes	
Transmission speed, min.	9.6 kbit/s	
Transmission speed, max.	12 Mbit/s	
Automatic detection of transmission speed	-	
Transfer memory inputs, max.	244 Byte	
Transfer memory outputs, max.	244 Byte	
Address areas, max.	32	
User data per address area, max.	32 Byte	
Point-to-point communication		
PtP communication	yes	
Interface isolated	yes	
RS232 interface	-	
RS422 interface	-	
RS485 interface	yes	
Connector	Sub-D, 9-pin, female	
Transmission speed, min.	150 bit/s	
Transmission speed, max.	115.5 kbit/s	
Cable length, max.	500 m	
Point-to-point protocol		
ASCII protocol	yes	
STX/ETX protocol	yes	
3964(R) protocol	yes	
RK512 protocol	-	
USS master protocol	yes	
Modbus master protocol	yes	
Modbus slave protocol	-	
Special protocols	-	
Functionality RJ45 interfaces		
Туре	X5	

[©] by VIPA GmbH, Ohmstr. 4, 91074 Herzogenaurach, Germany All data with reservation and subject to change. Publish date: 26.07.2016



Type of interface	Ethernet 10/100 MBit	A YASKAWA COMPANY
Connector	RJ45	
Electrically isolated	yes	
PG/OP channel	yes	
Number of connections, max.	4	
Productive connections	-	
Housing		
Material	PPE	
Mounting	Rail System 300	
Mechanical data		
Dimensions (WxHxD)	80 mm x 125 mm x 120 mm	
Weight	480 g	
Environmental conditions		
Operating temperature	0 °C to 60 °C	
Storage temperature	-25 °C to 70 °C	
Certifications		
UL certification	yes	
KC certification	yes	