

## Data sheet

### Panel PC PPC015 ES (67P-PNL0-JB)

#### Technical data

<b>Order no.</b>	<b>67P-PNL0-JB</b>
Type	Panel PC PPC015 ES

#### General information

Note	-
Features	<p>Processor: Intel Atom D2550 dualcore @1.86 GHz          Work memory: 2 GB          Operating system and user memory: 16 GB          Memory card plug-in place: CFast          Interfaces: 2x Ethernet (10/100/1000), 4x USB 2.0, 2x serial (RS232,RS422/RS485), Audio out          Display: 15.6"          Incl. operating system Windows Embedded Standard 7 and Runtime Movicon 11 Win Standard, 32 I/O Bytes?</p>

#### Display

Display size (diagonal)	15.6 "
Display size (width)	344 mm
Display size (height)	195 mm
Resolution	1366 x 768
Aspect ratio	16:9
Type of display	TFT color (16.7M colors)
MTBF Backlights (25°C)	50000 h

#### System properties

Processor	Intel Atom Dualcore 1.86 GHz
Operating system	Windows embedded Standard 7
User software	Movicon 11 Win Standard
Work memory	2 GB
User memory	16 GB
Available memory (user data)	7 GB
SD/MMC Slot	-
CF Card Slot Typ II	-
CFast Slot	yes

#### Time

Real-time clock buffered	yes
Clock buffered period (min.)	4 y
Type of buffering	lithium battery
Load time for 50% buffering period	-
Load time for 100% buffering period	-
Accuracy (max. deviation per day)	10 s

#### Operating controls

Touchscreen	PCAP
Touch function	Dual Touch
Keyboard	external via USB
Mouse	external via USB

## Interfaces

MPI, PROFIBUS-DP	-
MPI, PROFIBUS-DP connector	-
Serial, COM1	RS232 / RS422 / RS485
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS232 / RS422 / RS485
COM2 connector	Sub-D, 9-pin, male
Number of USB-A interfaces	4
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	2
Ethernet	Ethernet 10/100/1000 MBit
Ethernet connector	2 x RJ45
Integrated ethernet switch	-
Video connectors	VGA SubD HD15
Audio connections	Line out, stereo jack 3.5 mm

## Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	1.2 A
Current consumption (rated value)	1.3 A
Inrush current	1.3 A
I <sub>Δt</sub>	0.35 A <sup>2</sup> s
Power loss	32 W

## Status information, alarms, diagnostics

Supply voltage display	none
------------------------	------

## Mechanical data

### Housing / Protection type

Material	coated aluminium steel plate
Mounting	via integrated pivoted lever
Protect type front side	IP 65
Protect type back side	IP 20

### Dimensions

Front panel	417.8 mm x 312.8 mm x 6.2 mm
Rear panel	396 mm x 291 mm x 57.6 mm

### Installation cut-out

Width	401 mm
Height	296 mm
Minimum	3 mm
Maximum front panel thickness	12 mm
Weight	6.2 kg

### Environmental conditions

Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 75 °C

### Certifications

UL certification	yes
KC certification	-