

Data sheet

TM-C Router (900-2C610)

Technical data

Order no.	900-2C610
------------------	------------------

Type	TM-C Router
------	-------------

General information

Note	-
------	---

Features	For teleservice through broadband connection via Talk2M 1x RS485 MPI-/PROFIBUS-DP interface 4x LAN RJ45 Ethernet interface 1x WAN RJ45 Ethernet interface
----------	--

Inputs and outputs

Inputs	1 DI: 0/24 V DC, isolated
--------	---------------------------

Outputs	1 DO: open drain, max. 200 mA at DC 30 V
---------	--

Communication

serial port	MPI/PROFIBUS, isolated, up to 12 MBit/s
-------------	---

LAN	4 x RJ45, 10/100 MBit/s Switch
-----	--------------------------------

WAN	1 x RJ45, 10/100 MBit/s
-----	-------------------------

Modem type	-
------------	---

Router

Router functions	Talk2M
------------------	--------

RAS	-
-----	---

VPN

VPN mode	-
----------	---

Talk2M	yes
--------	-----

Gateway protocols	-
-------------------	---

Services

Server services	FTP HTTP
-----------------	-------------

Client Services	-
-----------------	---

Data management

Custom Website	yes
----------------	-----

Project	web interface
---------	---------------

Integrated protocols	-
----------------------	---

Interrupts

Alarm message	-
---------------	---

Alarm	-
-------	---

Housing

Material	-
----------	---

Mounting	Profile rail 35 mm
----------	--------------------

Mechanical data

Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
--------------------	-------------------------

Weight	410 g
--------	-------

Environmental conditions

Operating temperature	-20 °C to 70 °C
-----------------------	-----------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

Certifications

UL certification	-
------------------	---

KC certification	-
------------------	---