

Data sheet

- (900-2H682)

Technical data

Order no.	900-2H682
Type	-
General information	
Note	-
Features	-
Inputs and outputs	
Inputs	-
Outputs	-
Communication	
serial port	-
LAN	4 x RJ45, 10/100 MBit/s Switch
WAN	1 x RJ45, 10/100 MBit/s
Modem type	HSUPA
Router	
Router functions	IP-Forwarding IP-Filter NAT Port-Forwarding Routing Table DHCP-Client
RAS	PPP Dial-In PPP Dial-Out Call-Back
VPN	
VPN mode	-
Talk2M	-
Gateway protocols	MPI PPI PROFIBUS ISO TCP Modbus TCP
Services	
Server services	FTP HTTP
Client Services	FTP SMTP NTP DYNDNS SNMP
Data management	
Custom Website	-
Project	web interface
Integrated protocols	MPI MPI PROFIBUS ISO TCP Modbus TCP

Interrupts

Alarm message	E M a i l S M S S N M P F T P
Alarm	E M a i l H a r d w a r e I / O S M S P L C - v a r i a b l e s S N M P s y s t e m v a r i a b l e s F T P

Housing

Material	-
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	39 " x 129 " x 108 "
Weight	480 g

Environmental conditions

Operating temperature	-20 °C to 70 °C
Storage temperature	-

Certifications

UL certification	-
KC certification	-